

v 2.0 2019



Monocular microscope, 400x, rechargeable, N-PLAN objectives

Observation Method - Transmitted Light	Brightfield	Yes
	Simple polarized light	As optional
Main Body	Туре	Upright
	Construction material	Aluminum die-cast
Head	Туре	Monocular
	Inclination	30°
	360° rotating	Yes
	Fixing screw for eyepieces	Yes
	Tube inner diameter (mm)	23
Eyepieces	Field number (mm)	18
	Magnification	10x
	High eyepoint (for glass wearers)	Yes
	Pointer	As optional
	Micrometric scale	As optional
	Diameter of micrometer glass (mm)	20
Nosepiece	Positions	Quadruple
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS
Objectives	Optical system	160
	Anti-fungus treatment	Yes
	Parfocal distance (mm)	45
	Standard magnifications	40x-400x
	Туре	N-PLAN
	Objectives included	4x/0.10, W.D. 15.2 mm
		10x/0.25, W.D. 5.5 mm
		40x/0.65, W.D. 0.45 mm
Stage	Туре	Fixed
	Dimensions (mm)	130x120
	Moving mechanism	As optional
	Material	Anti-scratch painting
	Specimen clips	Yes
	Slide number	1
Condenser - Single Position	Туре	Fixed
	Numerical aperture (N.A.)	0.65
	Diaphragms	Iris
	Centrable	Pre-centered

Focusing System	Туре	Coaxial coarse & fine
	Coarse total travel (mm)	16
	Fine total travel (per single rotation) (mm)	0.4
	Fine graduations	100
	Fine resolution (µm)	4
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes
Transmitted Illumination	Туре	X-LED
	X-LED type	X-LED1
	Light source power (W)	1
	Brightness control	Manual
	Lifetime (hours)	> 65,000
	Temperature (K)	6,300
	Max. required power (W)	1.5
Power Supply for	Туре	External
Transmitted	Microscope connector	Jack, 2.1 mm
Illumination	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 500 mA
	LED indicator	Yes
	Rechargeable batteries	Yes
	Battery type	Li-ion (battery pack)
	Working time of batteries (hours)	15
	Charging time of batteries (hours)	6
Accessories Included	Dust cover	Yes
	Tension adjustment tool	Yes
	User Manual	Digital version (downloadable)
	osi manaa	Digital Foliatif (devilledadale)
Additional Information		Mirror for transmitted light (as optional)
Product Dimensions	Height (mm)	350
	Width (mm)	170
	Depth (mm)	320
<b>Product Weight</b>	(kg)	4